

Specifications - Multi-Position Series (3 Positions) - WML,

MODEL	ITEM NUMBER	FIRING RATE GPH	INPUT/ OUTPUT MBH	AFUE-CHIMNEY VENT				AFUE - DIRECT	
				BECKETT AF	BECKETT NX	RIELLO 40F3	RIELLO 40F5	BECKETT AFII-85	BECKETT AFII-150
WML60C2	34306080	0.50	70/59	83.3%					
WML60C2*	34306040	0.50	70/59	83.3%					
WMLV60C2	34306076	0.50	70/59	83.3%					
WMLV60C2*	34306046	0.50	70/59	83.3%					
WML80CNX2	34308085	0.65	91/77		85.5%				
WML60CNX2	Alternate Firing Rate	0.50	70/60		86.3%				
WML90CNX2		0.75	105/88		85.0%				
WMLV80CNX2	34308090	0.65	91/77		85.5%				
WMLV60CNX2	Alternate Firing Rate	0.50	70/60		86.3%				
WMLV90CNX2		0.75	105/88		85.0%				
WML80CRF2	34308073	0.65	91/76			83.3%			
WML60CRF2	Alternate Firing Rate	0.51	71/61			85.2%			
WML90CRF2		0.75	105/88			83.4%			
WMLV80CRF2	34308078	0.65	91/76			83.3%			
WMLV60CRF2	Alternate Firing Rate	0.51	91/76			85.2%			
WMLV90CRF2		0.75	105/88			83.4%			
WML80CB2U2	34308072C	0.65	91/76					83.6%	
WML60CB2U2	Alternate Firing Rate	0.55	77/63					84.1%	
WML90CB2U2		0.75	105/85					83.6%	
WMLV80CB2U2	34308077C	0.65	91/76					83.6%	
WMLV60CB2U2	Alternate Firing Rate	0.55	77/63					84.1%	
WMLV90CB2U2		0.75	105/85					83.6%	
WML80CRBU2	34308074C	0.65	91/78						
WML60CRBU2	Alternate Firing Rate	0.51	71/62						
WML90CRBU2		0.75	105/89						
WMLV80CRBU2	34308079C	0.65	91/78						
WMLV60CRBU2	Alternate Firing Rate	0.51	71/62						
WMLV90CRBU2		0.75	105/89						
MPL120B2	34312070	1.00	140/118	83.3%					
MPL90B2	Alternate Firing Rate	0.75	105/90	85.0%					
MPL100B2		0.85	119/97	83.2%					
MPL120BRF2	34312073	1.00	140/117				83.8%		
MPL90BRF2	Alternate Firing Rate	0.75	105/92				86.6%		
MPL100BRF2		0.85	119/101				83.7%		
MPL130BRF2		1.10	154/127				83.0%		
MPL120BB2U2	34312072C	1.00	140/118						84.8%
MPL90BB2U2	Alternate Firing Rate	0.75	105/88						83.6%
MPL100BB2U2		0.85	119/101						84.5%

BOLD TYPE indicates factory-equipped firing rate. Other firing rates shown utilize field-supplied nozzles.

* With Vestibule