

325 COMMERCE DRIVE MT VERNON, OH 43050 800-253-8236

## SPECIFICATION DATA SHEET

DATE: 4-5-13 PREPARED BY: RL

# MODEL NO. 015

## DRAWBAND

STANDARD MODEL

DIMENSIONS				
	····	* MIN	** MAX	
Α	В	øΑ	øΑ	
4"	6"	3 1/4"	4 1/4"	
5"	6"	4 1/4"	5 1/4"	
6"	6"	5 1/4"	6 1/4"	
7"	6"	6 1/4"	7 1/4"	
8"	6"	7 1/4"	8 1/4"	
10"	6"	9 1/4"	10 1/4"	
12"	6"	11 1/4"	12 1/4"	
14"	6"	13 1/4"	14 1/4"	
16"	6"	15 1/4"	16 1/4"	
	4" 5" 6" 7" 8" 10" 12"	A B 4" 6" 5" 6" 6" 6" 7" 6" 8" 6" 10" 6" 12" 6"	* MIN A B Ø A 4" 6" 3 1/4" 5" 6" 4 1/4" 6" 6" 5 1/4" 7" 6" 6 1/4" 8" 6" 7 1/4" 10" 6" 9 1/4" 12" 6" 11 1/4" 14" 6" 13 1/4"	

#### MATERIAL SPECIFICATIONS

HOT DIPPED GALVANIZED STEEL. PER ASTM A 653 CSB.

ASSEMBLED WITH 1/8" ZINC COATED RIVETS.

4" - 8" = STD GAUGE CONSTRUCTION 10" - 16" = 28 GAUGE CONSTRUCTION

TIPS/STRAPS ARE ZINC PLATED STEEL

STRAP  5/16" HEX HEAD  N/H2 PHILLIPS DRIVE  TIP		9/16"	B +
---	--	-------	-----

- \* MINIMUM ØA IS WHEN STRAP IS TIGHTENED AS FAR POSSIBLE.
- \*\* MAXIMUM ØA IS WHEN STRAP IS THE LARGEST DIAMETER WHERE STRAP WILL STILL LOCK INTO TIP

### OPTIONS

AVAILABLE IN 24GA BLACK HEAVIER GAUGES AVAILABLE