

MODELS PCD110X, PCD110XM, PCD110XH, PCD110XMH, & PCD110XIAQS

CEILING MOUNT BATHROOM FANS WITH DC MOTOR

Features and Construction

- Extremely quiet operation 0.5 Sones
- Brushless DC Motor for long life - rated for 60,000 hours continuous on
- PCD110XM has a built-in motion sensor and LED night light
- PCD110XH has a built-in humidity sensor
- PCD110XMH has a built-in motion sensor and humidity sensor
- PCD110XIAQS detects VOCs and/or rapid rise in humidity
- High/Low speed delay timer
- Built-in backdraft damper
- Robust steel housing
- Attractive, sturdy grille
- ETL Listed
- ENERGY STAR® qualified
- HVI Certified
- 6 year warranty



Performance and Dimensions

PCD110, PCD110M, PCD110H & PCD110IAQS					
CFM @ 0.1" SP	6" Duct	90	110	120	140
CFM @ 0.25" SP	6" Duct	64	77	89	100
Sones @ 0.1" SP	6" Duct	0.3	0.5	0.8	1.1
Watts @ 0.1" SP	6" Duct	5.5	10	11.5	14.5
Energy Efficiency (CFM/Watt)	6" Duct	16.4	11	10.4	9.7
Amps		.16	.18	.22	.23
ENERGY STAR Qualified	Yes				
Duct Connector Diameter (in)	6"				
Grille Size (in)	13" x 14"				
Dimensions (w x d x h) (in)	11-3/8" x 10-1/2" x 7-5/8"				

You CHOOSE Your Airflow!

The built-in **Toggle Switches** and duct connector options allow you to set the PCD110, PCD110M & PCD110H to the needed airflow.

1	2	3	1	2	3	1	2	3	1	2	3
90	110	120	140								
6"	6"	6"	6"								

1 & 2: Airflow • 3: Duct size
Factory setting is 110 CFM with 6" duct

Integrated Controls

