

OPX-400CS

VIOLET LIGHT LED LEAK DETECTION FLASHLIGHT



3
AAA
BATTERIES

25' Range
(8 m)

VIOLET
LIGHT
LED

UNIVERSAL (POE)
DYES ONLY

OPTIMAX™ 400

Economical and powerful, violet light LED leak detection flashlight.
Reveals even the smallest refrigerant leaks!

Features:

- ▶ Provides optimal fluorescent dye response and contrast
- ▶ Power comparable to 150W lamps
- ▶ Works with universal/POE dyes only
- ▶ Pre-focused beam optimizes fluorescent response
- ▶ Compact design easily gets into tight, cramped spaces
- ▶ Rugged, corrosion-resistance anodized lamp body stands up to years of heavy use
- ▶ Includes lanyard, belt holster and fluorescence-enhancing glasses

LAMP SPECIFICATIONS

Light Source	Violet Light LED
Lamp Style	Cordless flashlight
Lamp Head Diameter	1.29 in (3.2 cm)
Length	5.5 in (14 cm)
Weight	5.1 oz (0.14 kg)
Power Source	(3) "AAA" batteries
Run Time	5 hours (continuous)

NOTE: For most applications, our 400 Series lamps do not require fluorescence-enhancing glasses.

COMPLETE LEAK DETECTION KITS



OPK-40EZ/E Complete EZ-Ject™ Kit

Features the **OPX-400 OPTIMAX™ 400**, economical, cordless, battery operated, violet light LED leak detection flashlight.

- ▶ **EZ-50** EZ-Ject™ dye injector assembly
- ▶ **EZ-25** hose/coupler with check valve, low-loss and purge fittings
- ▶ (2) **EZ-4/E** 0.5 oz (15 ml) universal/POE dye cartridges



EACH EZ-4/E CARTRIDGE TREATS UP TO:

Lubricant: 2 gallons (7.6 L)
Refrigerant: 25 lbs (11.3 kg)
Cooling: 12 tons



(HTX-2 & HX-2)



OPK-40GS/E Complete GLO-STICK® Kit

Features the **OPX-400 OPTIMAX™ 400**, economical, cordless, battery operated, violet light LED leak detection flashlight.

- ▶ **BV-50** bleed valve for attaching GLO-STICK® capsule to service hose
- ▶ **EZ-25** hose/coupler with check valve, low-loss and purge fittings
- ▶ (1) **GS-1/E** 0.5 oz (15 ml) universal/POE GLO-STICK® dye capsule
- ▶ (2) **GS-2/E** 0.5 oz (15 ml) universal/POE GLO-STICK® dye capsules
- ▶ (1) **GS-3/E** 0.5 oz (15 ml) universal/POE GLO-STICK® dye capsule



GS-1/E: Treats 15.1 oz-1.6 qt (445 ml-1.5 L) of lubricant or 3-4.9 lb (1.4-2.2 kg) of refrigerant
GS-2/E: Treats 1.7-3.2 qt (1.6-3 L) of lubricant or 5-9.9 lbs (2.3-4.5 kg) of refrigerant
GS-3/E: Treats 3.3 qt-2 gal (3.1-7.6 L) of lubricant or 10-25 lbs (4.6-11.3 kg) of refrigerant



(HTX-2 & HX-2)



OPK-400BEZ/E Complete BigEZ™ Kit

Features the **OPX-400 OPTIMAX™ 400**, economical, cordless, battery operated, violet light LED leak detection flashlight.

- ▶ **BEZ-50** BigEZ™ dye injector assembly
- ▶ **BEZ-25** hose/coupler with check valve, low-loss and purge fittings
- ▶ (1) **BEZ-4/E** 4 oz (118 ml) universal/POE dye cartridge



EACH BEZ-4/E CARTRIDGE TREATS UP TO:

Lubricant: 16 gallons (61 L)
Refrigerant: 400 lbs (181 kg)
Cooling: 150 tons



(HTX-2 & HX-2)

SPECTRONICS
CORPORATION

www.spectroline.com

956 Brush Hollow Rd, Westbury, NY 11590 USA
800-274-8888 • 516-333-4840

DISTRIBUTED BY:

FOLLOW US:



HVAC/R
12/17 A17335
PRINTED IN USA