

## ACCESSORIES & DAMPER MOTORS



### MODEL AFC ANTI-FREEZE CONTROL

The AFC, recommended for by-passing air into return ducts, prevents air conditioning coils from freezing due to low air flow/refrigerant pressure, dirty filters, etc. Snaps onto suction line, breaks compressor circuit when suction line drops below 38° F, and recreates circuit at 48°F.



### MODELS ZPS AND OAS

The Zone Plenum Sensor is a duct-mounted sensor used with any current zoning panel and is mounted in the plenum area to avoid over-heating or cooling limits of HVAC system.

The Outdoor Air Sensor is mounted externally, ideally on building's north side and away from direct sunlight, and used with dual-fuel heat pump to switch between heat pump and furnace, depending on outdoor temperature.



### MODEL T24 24 VOLT 40VA TRANSFORMER

The T24 is a plate-mounted, step-down transformer – from typical 110/120VAC line voltage to 24VAC – and is rated at 40VA. It can be used to power all ZONEFIRST panels and 24V dampers.



### MODEL 4PDR 4 POLE DOUBLE THROW RELAY

The 4PDR is a 24VAC, four-pole double-throw relay that can be used whenever special applications require additional control switching or isolation.



### MODEL PIRR 24VAC PLUG-IN REPLACEMENT RELAY

The PIRR is the 24VAC plug-in relay used in the 4PDR accessory relay and can be used with older Trol-A-Temp™ zoning panels.